

Domestic and underfloor "Performance Plus" heat pumps								
Model number	Heat Pump Water Connection	Recommended flow rate						
DHW150	PT3/4"(20 mm male)	0.3 l/sec						
HW150U	20 mm female faucet coupling	0.3 l/sec						
DHW225	PT 1"(25 mm male)	0.45 l/sec						
HW225U	20 mm female faucet coupling	0.45 l/sec						
DHW275	PT 1"(25 mm male)	0.55 l/sec						
HW275U	25 mm female faucet coupling	0.55 l/sec						
DHW300 & DHW303	PT 1"(25 mm male)	0.6 l/sec						
HW300U & HW303U	25 mm female faucet coupling	0.6 l/sec						
DHW350 & DHW353	PT 1"(25 mm male)	0.7 l/sec						
HW350U & HW353U	25 mm female faucet coupling	0.7 l/sec						
DHW450 & DHW453	PT 1"(25 mm male)	0.9 l/sec						
DHW475	PT 1"(25 mm male)	1.2 l/sec						
HW475U	25 mm female faucet coupling	1.2 l/sec						
DHW550	PT 1"(25 mm male)	1.2 l/sec						
HW550U	25 mm female faucet coupling	1.2 l/sec						
DHW650	PT 1"(25 mm male)	1.4 l/sec						
HW650U	25 mm female faucet coupling	1.4 l/sec						
DHW800	PT 1"(25 mm male)	1.6 l/sec						
HW800U	25 mm female faucet coupling	1.6 l/sec						
DHW1050	PT 1"(25 mm male)	2.1 l/sec						
HW1050U	25 mm female faucet coupling	2.1 l/sec						
DHW1250	PT 1 1/2"(32 mm male)	2.5 l/sec						
HW1250U	25 mm female faucet coupling	2.5 l/sec						
<i>Note: DHWXXX-Domestic model range. HWXXXU-Underfloor heating model range</i>								
<i>Note: Materials and specifications are subject to change without notice due to the manufacturer's ongoing research and development program</i>								
<i>Manufacturer: Hot Water Heat Pumps Ltd, PO Box 21-586, Henderson, Auckland Tel: 09-838-9444 Fax: 09-838-6223</i>								